US007045008B2

(12) **United States Patent**
Langford

(10) **Patent No.: US 7,045,008 B2**
(45) **Date of Patent: May 16, 2006**

(54) **LOW DUST WALL REPAIR COMPOUND**

(75) Inventor: **Nathaniel P. Langford**, Somerset, WI (US)

(73) Assignee: **3M Innovative Properties Company**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/664,142**

(22) Filed: **Sep. 17, 2003**

(65) **Prior Publication Data**

US 2004/0063836 A1 Apr. 1, 2004

Related U.S. Application Data

(60) Continuation of application No. 09/781,386, filed on Feb. 12, 2001, which is a division of application No. 09/208,782, filed on Dec. 10, 1998, now Pat. No. 6,358,309.

(51) **Int. Cl.**

C04B 24/08	(2006.01)
C04B 26/02	(2006.01)
C04B 28/14	(2006.01)
C04B 103/00	(2006.01)
C04B 111/72	(2006.01)

(52) **U.S. Cl.** **106/504**; 106/661; 106/665; 106/773; 106/778; 106/822; 252/88.1; 524/4; 524/5

(58) **Field of Classification Search** 252/88.1; 106/504, 661, 665, 773, 778, 822; 524/5, 524/4

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,984,269	A	10/1976	Schneller et al.	
4,038,443	A	7/1977	Jacoby	
4,136,050	A	1/1979	Brehm	
4,171,276	A	10/1979	Brehm	
4,238,239	A	12/1980	Brown	
4,269,721	A	5/1981	Mueller et al.	
4,286,995	A *	9/1981	Smith et al.	106/778
4,294,622	A	10/1981	Brown	
4,316,811	A	2/1982	Burns et al.	
4,369,121	A	1/1983	Callahan et al.	
4,370,167	A	1/1983	Mudd	
4,380,459	A	4/1983	Netting	
4,391,647	A	7/1983	Deer et al.	
4,400,220	A	8/1983	Cole, Jr.	
4,417,992	A	11/1983	Bhattacharyya et al.	
4,425,252	A	1/1984	Cargle et al.	
4,428,984	A	1/1984	Shimizu et al.	
4,451,605	A	5/1984	Theodore	
4,454,267	A *	6/1984	Williams	524/43
4,469,612	A	9/1984	Fenton	
4,487,615	A	12/1984	Taylor et al.	
4,549,966	A	10/1985	Beall	
4,551,261	A	11/1985	Salihar	
4,551,401	A	11/1985	Wilson	
4,561,905	A	12/1985	Kittle	
4,571,116	A	2/1986	Patil et al.	
4,650,598	A	3/1987	Roberts et al.	
4,686,253	A *	8/1987	Struss et al.	524/44
4,737,305	A	4/1988	Dohner	
4,780,143	A	10/1988	Roe	
4,780,233	A	10/1988	Roe	
4,782,632	A	11/1988	Matechuk	
4,801,635	A	1/1989	Zinkan et al.	
4,836,945	A	6/1989	Kestner	
4,897,218	A	1/1990	Roe	
4,955,748	A	9/1990	Krumholz	
4,960,532	A	10/1990	Kremer	
4,971,720	A	11/1990	Roe	
4,972,013	A	11/1990	Koltisko, Jr. et al.	
4,981,398	A	1/1991	Field et al.	
5,007,206	A	4/1991	Paterson	
5,102,462	A	4/1992	Podlas	
5,131,198	A	7/1992	Ritchie et al.	
5,143,645	A	9/1992	Roe	
5,192,337	A	3/1993	Wajer et al.	
5,194,174	A	3/1993	Roe et al.	
5,246,775	A	9/1993	Loscuito	
5,256,444	A	10/1993	Roe	
5,277,712	A	1/1994	McInnis	
5,336,318	A	8/1994	Attard et al.	
5,362,320	A	11/1994	Whatcott	
5,382,287	A	1/1995	Podlas	
5,399,282	A	3/1995	Hansen et al.	
5,412,007	A	5/1995	Hendrix et al.	
5,439,608	A	8/1995	Kondrats	

(Continued)

FOREIGN PATENT DOCUMENTS

CA	111989	2/1982

(Continued)

Primary Examiner—Kelechi C. Egwim
(74) *Attorney, Agent, or Firm*—David B. Patchett

(57) **ABSTRACT**

A wall repair compound useful for filling and repairing cracks, holes, and other imperfections in a wall surface includes a conventional filler material, a conventional binder material, and a dust reducing additive which reduces the quantity of airborne dust particles generated when sanding the hardened joint compound. Airborne dust reducing additives include oils, surfactants, solvents, waxes, and other petroleum derivatives. The additive can be added to conventional ready-mixed joint compounds and to setting type joint compounds. A method of reducing the quantity of airborne dust generated when sanding a fully hardened joint compound includes mixing a sufficient quantity of the dust reducing additive with the joint compound prior to when the joint compound has been applied to the wall.

20 Claims, 1 Drawing Sheet